

# OEI-372S-H-W Indoor Station

## Overview

OEI-372S-H-W indoor station is one of the terminals in the digital building intercom system, with functions of video intercom, security alarm, network camera monitoring, etc., providing a safe and comfortable living environment for residents. It can be widely used in building systems such as smart communities, villas, and office parks.



## Features

- Rugged ABS casing and glass panel.
- 1024\*600 HD touch screen.
- Batch configuration transfer.
- Remote opening of linked door stations, one-key opening.
- Network camera monitoring, security alarm.

## Ordering Information

Model	Remarks
OEI-372S-H-W	Indoor Station

### Zhejiang Uniview Technologies Co., Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2022 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\* Product specifications and availability are subject to change without notice.

## Specifications

Parameter	Description
Power	DC12V±25%,IEEE802.3af, Standard PoE
Screen resolution	1024×600
Screen	7-inch ultra-thin TFT LCD screen
Operation system	Linux
Audio quality	Noise suppression,echo cancellation and AGC
Audio input	1 built-in omnidirectional microphone
Audio output	1 built-in speaker
Audio compression standard	MP3 G711
Audio compression rate	128Kbps
Protocol	UNV private protocol
Power consumption	<10W
Weight	360g
Interface	Power*1, network*1, Wi-Fi*1, RS485*1, IO output*2, IO input*8, TF card slot*1
Network	100Mbps network port, supports IEEE802.3af PoE power supply
Dimensions (L×H×W)	193mm×143mm×25mm
Operating environment	-10°C to +55°C, 10% to 90%, non-condensing, indoor

## Dimensions

