



AVC-EIPT51F28 AI

NDA
COMPLIANT | CE | FC


5MP EVO SERIES OUTDOOR FIXED TURRET NETWORK CAMERA

OVERVIEW

- 5MP @ 30fps
- Max. resolution: 2592x1944
- Supports H.265 / H.264 Video Compression
- 2.8mm Fixed Focal Lens
- Smart IR Illumination Up to 82ft (25m)
- Color / B&W (IR-CUT) Day & Night
- 3D DNR, WDR, ROI, HLC, and BLC Encoding
- Intelligent Analytics
- Built-in MIC
- PoE IEEE082.3af / DC12V±10%, 700mA
- IP67 Ingress Protection

DIMENSIONS

Unit : inch(mm)



OPTIONAL ACCESSORIES



AVM-JB-EVO-T1
JUNCTION BOX

SPECIFICATIONS

CAMERA	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS
Resolution	5MP
Main Stream	2592x1944, 2560x1440 @, 1920x1080, 1280x720 / @30fps
Sub Stream	1280x720, 720x480 / @30fps
Video Compression	HH.264 / H.265 Compression Available
Audio Compression	G.711a / G.711u, AAC
TV System	PAL / NTSC
Electronic Shutter Speed	Auto: 1/3 - 1/100,000s
Min. Illumination	Color: 0.006 Lux @ F1.6 (AGC ON), B/W: 0 Lux with IR
S/N Ratio	60dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
LENS	
Focal Length	2.8 mm
FOV	106° (H), 56° (V), 127° (D)
Lens Type	Fixed Focal Lens, 2.8mm
Focus Control	Fixed
Aperture	F1.6
Pixels	5MP
NIGHT VISION	
IR LED	42μ x 2PCS
IR Distance	82ft (25m)
IR Status	Auto Control
IR Power On	Smart, Manual, and Timed modes are available
IR Cut Filter	Yes
NETWORK	
Ethernet	RJ-45 (10/100Base-T)
Wireless	N/A
Protocol	TCP/IP, IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP, SNMP, Qos, 802.1x
ONVIF	Support ONVIF 19.12 (Profile S/T/G)
P2P	Yes
PoE	Internal, Support IEEE 802.3af
Video Delay	0.3s (Within the LAN)
IE Browser	IE8-11, Chrome, Firefox, and Mac Safari
AI FUNCTION	
Intelligent Analytics	Human & Vehicle Detection, Intrusion Detection, Line Crossing Detection, Loiter Detection, People Gathering Detection, Motion Detection
CAMERA FEATURES	
Day/Night	Color / B&W (IR-CUT)
Image Configuration	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D DNR, White Balance, Anti Flicker, Video Tampering, HLC
Corridor Pattern	Yes
ROI	Yes
BLC	Yes
WDR	True WDR
Motion Detction	Supported (Enables the detection based on Human Movement only)
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR / CMS / Web
Language	English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Chinese, Italian, Netherlands, Czech, Vietnamese
INTERFACE	
Audio	Built-in Mic
Alarm	N/A
RS485	N/A
GENERAL	
Housing	Metal, IP67
Anti-cut Bracket	NO
Operation Temperature	-4°~140°F (-20°~60°C) / less than ≤ 95% RH
Storage Temperature	-4°~140°F (-20°~60°C) / less than ≤ 95% RH
Power Source	PoE IEEE802.3af / DC12V±10%, 700mA
Dimensions	Ø3.78x3.58in (Ø96.0x91.0mm)
Weight	1.32lbs (600g)