



PDU20MVHVIEC38F Metered PDU

Engineered to distribute UPS, generator or utility AC power to multiple devices, servers and network/telecom equipment.

The CyberPower 38-outlet (38 Front) OU vertical rack mount basic power distribution unit (PDU20MVHVIEC38F) provides 200/230V 20A output. It distributes power to 38 IEC-320 (8-C19 and 30-C13) receptacles from a single IEC-320 C20 plug, with unfiltered electrical pass-through. The current draw for connected equipment is displayed in amps on the front LCD for real-time load monitoring.

Designed for datacenters and other electrically demanding applications, this unit has a rugged, industrial-grade metal housing and a 10-foot AC power cord. It supports vertical, horizontal and wall mount installation, includes a cord retention tray and is ETL/RoHS certified.

A Lifetime Warranty ensures that this PDU is free of defects in design, assembly, material and workmanship.

Typical Applications

- Servers
- Network Devices
- Telecom Equipment

Features

- Metered PDU
- Real-Time Load Monitoring
- Industrial-Grade Metal Housing
- Lifetime Warranty

PDU20MVHVIEC38F Metered PDU

Engineered to distribute UPS, generator or utility AC power to multiple devices, servers and network/telecom equipment.

GENERAL	
Type	Metered PDU
Phase	Single Phase
INPUT	
Voltage	200V/230V
Frequency	50Hz/60Hz
Maximum Input Current	20A (Derated to 16A)
Plug Type	IEC-320 C20
Plug Style	Straight
Cord Length	10'
OUTPUT	
Nominal Output Voltage	200V/230V
Outlets - Total	38
Outlet Type	IEC-320 C19/C13
Outlets - Front	8(C19)+30(C13)
Outlets - Rear	0
Meter Readout	Amperage
Overload Protection	16A
PHYSICAL	
Rack Size	OU
Form Factors Supported	Vertical Rackmount, Wallmount
Cord Retention Organizers	Yes
External Site Ground Pin	Yes
Adjustable Mounting Brackets	3 sets (L-short, L-long, Flat)
Dimensions (WxHxD) (in.)	1.75 x 70 x 2.25
Weight (lbs.)	9.5
ENVIRONMENTAL	
Operating Temperature	32°F to 95°F / 0°C to 35°C
Operating Relative Humidity	0% - 95% non-condensing
Storage Temperature	5°F to 113°F / -15°C to 45°C
Maximum Operating Elevation	10,000 ft / 3,000 m
Maximum Storage Elevation	50,000 ft / 15,000 m
CERTIFICATIONS	
Safety	UL60950_1 certified by ETL (USA), CSA C22.2 (Canada)
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	Lifetime