# R71CF-35



#### 2MP

- Access Control with Card + Face Recognition (99%), Intercom Station
- 7" LCD Color Touch Screen
- Wiegand Reader and Controller
- Bundle with 20000 Face Database
- Built-in MIFARE Card Reading Module
- Not available in the USA

## Specifications

#### **Device**

Device Type  Access Controller RFID Reader Face Reader  Maximum Resolution  2MP  Product Application  Access Control with Card + Face Recognition (99%), Intercom Station  2MP Mifare LCD Card Face Recognition Wiegand Reader and Controller with Bundle 50,000 Card Database / 20,0  Face Database.
Product Application  Access Control with Card + Face Recognition (99%), Intercom Station  2MP Mifare LCD Card Face Recognition Wiegand Reader and Controller with Bundle 50,000 Card Database / 20,0  Face Database.
Description 2MP Mifare LCD Card Face Recognition Wiegand Reader and Controller with Bundle 50,000 Card Database / 20,0 Face Database.
Face Database.
To Color Touch Caroon, Decolition, 1024 v C00
LCD Screen 7" Color Touch Screen; Resolution: 1024 x 600
Lens
Number of Lenses 2 Lenses
Focal Length Fixed focal
Video
Built-in Analytics Face Recognition, RFID Recognition
Audio
Audio Type 2-way, Built-in Microphone, Built-in Speaker
Network
Ethernet Port 1 x Ethernet (10/100/1000 Base-T), RJ-45 connector

#### **Video Analytics**

Analysis Source Type	Video, Image
Metadata Accuracy	Excellent
Face Recognition Distance	0.3m - 3m

#### **Event**

Event Log 100,000

#### **System**

Operating System Linux

## **Access Control Functionality**

Access Mode Card only, Face only, Card and Face	
---	--

#### **RFID Card**

Communication Frequency	13.56 MHz
RFID Standard	ISO 14443A
RFID Options	MIFARE

#### **Storage**

User Database	Card Capacity: 50,000 Face Picture Capacity: 20,000
Card + Face Detection User Limit	20,000
Face Only Detection User Limit	20,000

#### Interface

Serial Port	1 x RS-485
Digital Input/Output	2/1

#### General

Power Source	DC 12V (adapter not included), 3 A
Dimensions	(W x H x D): 239mm x 116.5mm x 33mm (9.41" x 4.59" x 1.30")
Environmental Casing	Weather resistant (IP65)
Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F)
Operating Humidity	0% - 90% RH
Warranty	1 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty

### Related Products

#### **Access Control System - Access Card**

PACD-0004 RFID Card Mifare 13.56 MHz

#### **Power Supply Accessories - Power Adapter**

PPBX-0016



Power Adapter AC 100~240V (12V/5A Output), with universal connectors for R7 series